


CAT6 110- PUNCH DOWN TYPE IN-LINE SHIELDED COUPLER

- For extension or fan out of shielded CAT6 4-pair cable without RJ-45 connections.
- Shielded enclosure with one dedicated terminal for drain wire punch down.
- Wiring Scheme: Pin to Pin, universal for both 568A or 568B(258A) standard.
- Internal PCB (Printed Circuit Board) structure with chrome plated enclosure - meets EIA/TIA Cat6 specifications.
- Surface mountable enclosure with cable tie loops.
- Color-coded 110 punch down terminals.



ORDER CODE	1-49	50-99	100+
080-110-4-SH-C6	\$7.39	7.06	6.55



CAT6a 90° 110 TYPE MINI KEYSTONE JACK SHIELDED

- Exceeds TIA/EIA CAT6 specification to support 10G Base-Tand Gigabyte Ethernet system application
- Hardware certification comply with TIA/EIA-568-B.2-1 CAT6
- Mountable for all kinds of standard keystone jack opening
- Wire pins are plated with 50 micro inches gold over nickle
- 110 IDC accepts 23-24 AWG wires
- Available in both T568A and T568B universal wiring
- Product is RoHS Compliant
- Shielded

ORDER CODE	DESCRIPTION	1-49	50-99	100+
07E-188-M-C6A	Cat6a 90° 110 Type Mini Keystone Jack Shielded	\$11.00	10.50	9.75

CAT5E SHIELDED KEYSTONE JACKS

- True 110-Type IDC termination with strain-relief cap.
- Two-piece snap-on type metal enclosure provides 100% shielding.
- Unique cable entry holder to fit with different cable OD.
- Metal enclosure connects to pin in the 110 connector to provide drain wire direct connection.
- 50µ" gold plating on jack contacts - meet all FCC part 68 specification.
- UL Verified Cat5E - meet EIA/TIA TSB-40A specification.



ORDER CODE	DESCRIPTION	1-49	50-99	100+
07E-188-BK	CAT5E, 8P8C RJ-45	\$3.87	3.70	3.43
07E-188-C6	CAT6 110 90° Termination Keystone Jack	5.90	5.63	5.23

CAT6a SHIELDED SNAP-IN COUPLER PANEL MOUNTABLE

- Snap-in type enclosure allows easy mounting onto any keystone jack wall plate or panel.
- Shielded
- Compact Size: 0.57" (W) x 0.64" (H) x 1.18" (D)

SHIELDED CAT6 RJ45 IN-LINE COUPLER-PANEL MOUNTABLE

- Snap-In type enclosure allows easy mounting onto any Keystone Jack wall plates or panels.
- Fully shielded enclosure meets EMI/RFI requirements.

ORDER CODE	1-49	50-99	100+
080-885-C6-SI-SH	\$6.95	6.64	6.16

CAT5E SHIELDED MINI COUPLER

- Straight-thru pin-to-pin wiring configuration.
- Superior PCB design ensures highest performance.
- Meets EIA/TIA 568A Cat5E specifications.
- Shielded enclosure meets EMI/RFI requirements.
- Snap-in type enclosure allows easy mounting onto any keystone jack wall plates or panels.

ORDER CODE	1-49	50-99	100+
080-C5E-SI-SH-M	\$4.75	4.54	4.21

SHIELDED RJ-45 IN-LINE COUPLER

- Snap-in type design.
- Full metal enclosure, shielded.
- Pin-to-pin configuration.

ORDER CODE	1-49	50-99	100+
080-885-SI-SH	\$3.08	2.94	2.73

CAT6 SHIELDED PATCH CABLES

CAT6 CERTIFIED RJ-45 SHIELDED PATCH CABLES

- 26 AWG, stranded (7 x 32) bare copper, four twisted pair with aluminum mylar foil shielded, drain wire, ETL / UL verified, meets Category 6 specifications, tested to 550 MHz.
- Modular plug: Category 6 shielded long body 3 pieces stagger type RJ-45 plug with snag-free strain relief boot.
- Snag-free strain relief boot provides the most secure and accurate connection.
- Multi-colored jackets enhance network cabling management solutions.
- Meets and exceeds EIA/TIA 568A-4 Category 6 patch cable standards.
- FLUKE DSP-4300 100% tested and certified (4-25 feet only).



ORDER CODE	LENGTH	1-49	50-99	100+
05GH-01-A-YY/XX	1 foot	\$6.48	6.18	5.74
05GH-02-A-YY/XX	2 feet	6.79	6.48	6.02
05GH-03-A-YY/XX	3 feet	7.11	6.79	6.30
05GH-05-A-YY/XX	5 feet	7.74	7.39	6.86
05GH-07-A-YY/XX	7 feet	8.38	8.00	7.43
05GH-10-A-YY/XX	10 feet	9.33	8.90	8.27
05GH-14-A-YY/XX	14 feet	10.91	10.42	9.67
05GH-20-A-YY/XX	20 feet	12.50	11.93	11.08
05GH-25-A-YY/XX	25 feet	14.08	13.44	12.48
05GH-50-A-YY/XX	50 feet	22.00	21.00	19.50
05GH-75-A-YY/XX	75 feet	29.92	28.56	26.52
05GH-100-A-YY/XX	100 feet	37.84	36.12	33.54

XX = Boot Color	YY = Cable Color
WH - White	WH - White
GY - Gray	GY - Gray
BK - Black	BK - Black
BL - Blue	BL - Blue
PP - Purple	GN - Green
GN - Green	RD - Red
RD - Red	OR - Orange
OR - Orange	YL - Yellow
YL - Yellow	PK - Pink

• Custom Length: \$6.30 + \$0.32/feet



CABLES/ACCESSORIES

SHIELDED BULK CABLE

- 1000 feet per reel.

XX = Color	Colors on page
06F-R4P-T-24-XX-SH	31
06G-R4P-T-26-XX-SH	27

ORDER CODE	DESCRIPTION	PRICE
062-F4C-T-26-(SV/BK)-SH	4 Conductors, Flat, Silver or Black	PLEASE CALL US FOR PRICING
062-F6C-T-26-(SV/BK)-SH	6 Conductors, Flat, Silver or Black	
06F-R4P-T-24-XX-SH	CAT5E Stranded, 4-Pair, Round	
06F-R4P-S-24-GY-SH	CAT5E Solid, 4-Pair, Round, Gray	
06G-R4P-S-24-GY-SH	CAT6 Shielded Twist Pair, Solid, Gray	
06G-R4P-T-26-XX-SH	CAT6 Shielded Twist Pair, Stranded	

** Additional order in special colors are available. MOQ is 10,000 feet. **

SHIELDED RJ-45 MODULAR PLUGS

- 50µ" gold plating, for solid and or stranded cables.


ORDER CODE	DESCRIPTION	1-49	50-99	100+
060-R88-T-50-SH	8P8C, RJ-45 Stranded	\$0.53	0.50	0.47
060-R88-S-50-SH	8P8C, RJ-45 Solid	0.53	0.50	0.47
060-R88-T-50-C5E-SH	8P8C, CAT5E Stranded	0.88	0.84	0.78
060-R88-T-50-C6-SH	8P8C, CAT6 Stranded	1.41	1.34	1.25



CAT5E CABLES

MOLDED TYPE (SHIELDED) RJ-45 WITH SNAG FREE BOOT

- Molded strain relief with snag free cap from the cable entry to the end of plug.
- Cable: ETL/UL verified Cat5E, 24 AWG, stranded (7x32) bare copper, 4 twisted pairs with aluminum mylar foil shielded, drain wire.
- Staggered type Cat5E RJ-45 plug reduces NEXT.



ORDER CODE	LENGTH	1-49	50-99	100+
05BH-01-A-YY/XX	1 foot	\$4.66	4.45	4.13
05BH-02-A-YY/XX	2 feet	4.93	4.70	4.37
05BH-03-A-YY/XX	3 feet	5.19	4.96	4.60
05BH-05-A-YY/XX	5 feet	5.72	5.46	5.07
05BH-07-A-YY/XX	7 feet	6.25	5.96	5.54
05BH-10-A-YY/XX	10 feet	7.04	6.72	6.24
05BH-15-A-YY/XX	15 feet	8.36	7.98	7.41
05BH-20-A-YY/XX	20 feet	9.68	9.24	8.58
05BH-25-A-YY/XX	25 feet	11.00	10.50	9.75
05BH-50-A-YY/XX	50 feet	17.60	16.80	15.60
05BH-75-A-YY/XX	75 feet	24.20	23.10	21.45
05BH-100-A-YY/XX	100 feet	30.80	29.40	27.30

• Custom Length: \$5.00 + 0.30/ft

XX = Injection Mold Color	WH	BK	PP	RD	OR	IV
	GY	BL	GN	BR	YL	PK

YY = Cable Color	GY	BK	BL	GN	RD	OR	YL
------------------	----	----	----	----	----	----	----

Custom Wiring and Length Available

