


NULL MODEM CABLES



- Can be used for hardware flow control.
- Cross pinned wiring configuration.
- Fully molded hoods with thumbscrews.


NULL MODEM MOLDED CABLE (DB-25 / DB-25)

ORDER CODE	DESCRIPTION	1-24	25-49	50+
C09-25M-25M-06	DB-25 Male/DB-25 Male, 6 feet	\$2.82	2.69	2.50
C09-25M-25M-10	DB-25 Male/DB-25 Male, 10 feet	3.52	3.36	3.12
C09-25M-25M-15	DB-25 Male/DB-25 Male, 15 feet	4.49	4.28	3.98
C09-25M-25F-06	DB-25 Male/DB-25 Female, 6 feet	2.82	2.69	2.50
C09-25M-25F-10	DB-25 Male/DB-25 Female, 10 feet	3.52	3.36	3.12
C09-25M-25F-15	DB-25 Male/DB-25 Female, 15 feet	4.49	4.28	3.98
C09-25F-25F-06	DB-25 Female/DB-25 Female, 6 feet	2.82	2.69	2.50
C09-25F-25F-10	DB-25 Female/DB-25 Female, 10 feet	3.52	3.36	3.12




NULL MODEM MOLDED CABLE (DB-25 / DB-9)

ORDER CODE	DESCRIPTION	1-24	25-49	50+
C09-25M-09F-06	DB-25 Male/DB-9 Female, 6 feet	\$2.82	2.69	2.50
C09-25M-09F-10	DB-25 Male/DB-9 Female, 10 feet	3.52	3.36	3.12
C09-25M-09F-25	DB-25 Male/DB-9 Female, 25 feet	6.86	6.55	6.08
C09-25F-09F-06	DB-25 Female/DB-9 Female, 6 feet	2.82	2.69	2.50
C09-25F-09F-10	DB-25 Female/DB-9 Female, 10 feet	3.52	3.36	3.12



NULL MODEM MOLDED CABLE (DB-9 / DB-9)

ORDER CODE	DESCRIPTION	1-24	25-49	50+
C09-09M-09F-06	DB-9 Male/DB-9 Female, 6 feet	\$2.73	2.60	2.42
C09-09M-09F-10	DB-9 Male/DB-9 Female, 10 feet	3.52	3.36	3.12
C09-09F-09F-06	DB-9 Female/DB-9 Female, 6 feet	2.73	2.60	2.42
C09-09F-09F-10	DB-9 Female/DB-9 Female, 10 feet	3.52	3.36	3.12



SPEAKER CABLES




ORDER CODE	DESCRIPTION	1-24	25-49	50+
C27-SM-2RM-03	3.5mm Stereo Plug to 2 RCA Male, 3 feet	\$2.02	1.93	1.79
C27-SM-2RM-06	3.5mm Stereo Plug to 2 RCA Male, 6 feet	2.46	2.35	2.18
C27-SM-2RM-10	3.5mm Stereo Plug to 2 RCA Male, 10 feet	3.17	3.02	2.81
C27-SM-2RM-15	3.5mm Stereo Plug to 2 RCA Male, 15 feet	3.87	3.70	3.43
C27-SM-2RM-25	3.5mm Stereo Plug to 2 RCA Male, 25 feet	5.46	5.21	4.84
C27-RM-RM-03	RCA Male to Male Cable, 3 feet	0.88	0.84	0.78
C27-RM-RM-06	RCA Male to Male Cable, 6 feet	1.14	1.09	1.01
C27-RM-RM-10	RCA Male to Male Cable, 10 feet	1.50	1.43	1.33
C27-RM-RM-15	RCA Male to Male Cable, 15 feet	1.94	1.85	1.72
C27-RM-RM-25	RCA Male to Male Cable, 25 feet	2.73	2.60	2.42
C27-2RM-2RM-03	2 RCA Male to 2 RCA Male Cable, 3 feet	2.02	1.93	1.79
C27-2RM-2RM-06	2 RCA Male to 2 RCA Male Cable, 6 feet	2.46	2.35	2.18
C27-2RM-2RM-10	2 RCA Male to 2 RCA Male Cable, 10 feet	3.17	3.02	2.81
C27-2RM-2RM-15	2 RCA Male to 2 RCA Male Cable, 15 feet	3.87	3.70	3.43
C27-2RM-2RM-25	2 RCA Male to 2 RCA Male Cable, 25 feet	5.46	5.21	4.84
C27-SM-SF-03	3.5mm Stereo Plug to Jack Cable, 3 feet	1.67	1.60	1.48
C27-SM-SF-06	3.5mm Stereo Plug to Jack Cable, 6 feet	2.02	1.93	1.79
C27-SM-SF-10	3.5mm Stereo Plug to Jack Cable, 10 feet	2.46	2.35	2.18
C27-SM-SF-15	3.5mm Stereo Plug to Jack Cable, 15 feet	2.99	2.86	2.65
C27-SM-SF-25	3.5mm Stereo Plug to Jack Cable, 25 feet	4.22	4.03	3.74
C27-SM-SM-01	3.5mm Stereo Plug to Plug Cable, 1 foot	0.88	0.84	0.78
C27-SM-SM-03	3.5mm Stereo Plug to Plug Cable, 3 feet	1.67	1.60	1.48
C27-SM-SM-06	3.5mm Stereo Plug to Plug Cable, 6 feet	2.02	1.93	1.79
C27-SM-SM-10	3.5mm Stereo Plug to Plug Cable, 10 feet	2.46	2.35	2.18
C27-SM-SM-15	3.5mm Stereo Plug to Plug Cable, 15 feet	2.99	2.86	2.65
C27-SM-SM-25	3.5mm Stereo Plug to Plug Cable, 25 feet	4.22	4.03	3.74
C27-SM-2RF-03	3.5mm Stereo Plug to 2 RCA Female Cable, 3 feet	2.02	1.93	1.79
C27-SM-2RF-06	3.5mm Stereo Plug to 2 RCA Female Cable, 6 feet	2.46	2.35	2.18
C27-SM-2RF-10	3.5mm Stereo Plug to 2 RCA Female Cable, 10 feet	3.17	3.02	2.81
C27-SM-2RF-15	3.5mm Stereo Plug to 2 RCA Female Cable, 15 feet	3.87	3.70	3.43
C27-SM-2RF-25	3.5mm Stereo Plug to 2 RCA Female Cable, 25 feet	5.46	5.21	4.84
C27-2RM-2RF-03	2 RCA Male to 2 RCA Female Cable, 3 feet	2.02	1.93	1.79
C27-2RM-2RF-06	2 RCA Male to 2 RCA Female Cable, 6 feet	2.46	2.35	2.18
C27-2RM-2RF-10	2 RCA Male to 2 RCA Female Cable, 10 feet	3.17	3.02	2.81
C27-2RM-2RF-15	2 RCA Male to 2 RCA Female Cable, 15 feet	3.87	3.70	3.43
C27-2RM-2RF-25	2 RCA Male to 2 RCA Female Cable, 25 feet	5.46	5.21	4.84

SERIAL CABLES

AT SERIAL / MODEM CABLE (DB-25 / DB-9)

- 28 AWG foil shield construction.
- Fully molded hoods with thumbscrews.



ORDER CODE	DESCRIPTION	1-24	25-49	50+
C04-25M09F0901	DB-25 Male to DB-9 Female, 1 Foot	\$2.11	2.02	1.87
C04-25M09F0903	DB-25 Male to DB-9 Female, 3 feet	2.46	2.35	2.18
C04-25M09F0906	DB-25 Male to DB-9 Female, 6 feet	3.08	2.94	2.73
C04-25M09F0910	DB-25 Male to DB-9 Female, 10 feet	3.87	3.70	3.43
C04-25M09F0915	DB-25 Male to DB-9 Female, 15 feet	4.84	4.62	4.29
C04-25M09F0925	DB-25 Male to DB-9 Female, 25 feet	6.86	6.55	6.08
C04-25M09M0903	DB-25 Male to DB-9 Male, 3 feet	2.46	2.35	2.18
C04-25M09M0906	DB-25 Male to DB-9 Male, 6 feet	3.08	2.94	2.73
C04-25M09M0910	DB-25 Male to DB-9 Male, 10 feet	3.87	3.70	3.43
C04-25M09M0925	DB-25 Male to DB-9 Male, 25 feet	6.86	6.55	6.08
C04-25F09M0901	DB-25 Female to DB-9 Male, 1 Foot	2.11	2.02	1.87
C04-25F09M0906	DB-25 Female to DB-9 Male, 6 feet	3.08	2.94	2.73
C04-25F09M0910	DB-25 Female to DB-9 Male, 10 feet	3.87	3.70	3.43

RS-232 CABLE (DB-25 / DB-25)

- DB-25 Male to Male, Male to Female or Female to Female.



ORDER CODE	DESCRIPTION	1-24	25-49	50+
C03-25M25M2503	DB-25 Male to DB-25 Male, 3 feet	\$3.52	3.36	3.12
C03-25M25M2506	DB-25 Male to DB-25 Male, 6 feet	4.75	4.54	4.21
C03-25M25M2510	DB-25 Male to DB-25 Male, 10 feet	6.25	5.96	5.54
C03-25M25M2515	DB-25 Male to DB-25 Male, 15 feet	8.36	7.98	7.41
C03-25M25M2525	DB-25 Male to DB-25 Male, 25 feet	12.14	11.59	10.76
C03-25M25F2503	DB-25 Male to DB-25 Female, 3 feet	3.52	3.36	3.12
C03-25M25F2506	DB-25 Male to DB-25 Female, 6 feet	4.75	4.54	4.21
C03-25M25F2510	DB-25 Male to DB-25 Female, 10 feet	6.25	5.96	5.54
C03-25M25F2515	DB-25 Male to DB-25 Female, 15 feet	8.36	7.98	7.41
C03-25M25F2525	DB-25 Male to DB-25 Female, 25 feet	12.14	11.59	10.76
C03-25F25F2503	DB-25 Female to DB-25 Female, 3 feet	3.52	3.36	3.12
C03-25F25F2506	DB-25 Female to DB-25 Female, 6 feet	4.75	4.54	4.21
C03-25F25F2510	DB-25 Female to DB-25 Female, 10 feet	6.25	5.96	5.54
C03-25F25F2515	DB-25 Female to DB-25 Female, 15 feet	8.36	7.98	7.41
C03-25F25F2525	DB-25 Female to DB-25 Female, 25 feet	12.14	11.59	10.76

RS-449 SERIAL CABLE (DB-37 / DB-37)

- Fully molded hoods with thumbscrews.
- 28 AWG foil shield construction.



ORDER CODE	DESCRIPTION	UNIT PRICE
C21-37M37M3703	DB-37 Male to DB-37 Male, 3 feet	
C21-37M37M3706	DB-37 Male to DB-37 Male, 6 feet	
C21-37M37M3710	DB-37 Male to DB-37 Male, 10 feet	
C21-37M37F3703	DB-37 Male to DB-37 Female, 3 feet	
C21-37M37F3706	DB-37 Male to DB-37 Female, 6 feet	
C21-37M37F3710	DB-37 Male to DB-37 Female, 10 feet	

PLEASE CALL FOR PRICE

INTERFACE CABLES

IEEE-488, GPIB/HP/IB INTERFACE CABLE

- Centronics 24 Male + Female to Centronics 24 Male + Female.
- Metal Hood, Metric Jackscrews.

ORDER CODE	LENGTH	1-24	25-49	50+
C20-C24MF-1M	1 Meter	\$30.80	29.40	27.30
C20-C24MF-2M	2 Meters	35.20	33.60	31.20
C20-C24MF-4M	4 Meters	39.60	37.80	35.10
C20-C24MF-5M	5 Meters	46.20	44.10	40.95
C20-C24MF-8M	8 Meters	57.73	55.10	51.17

